

UP-Touch Panel DP 3.0 CAP 104, 150, 185, 215



UP-Touch Panel DP 3.0 CAP



UP-Touch Panel DP CAP 104
black Art-Nr. 04710 | white Art-No. 04715



UP-Touch Panel DP CAP 185
black Art-Nr. 04712 | white Art-No. 04717



UP-Touch Panel DP CAP 150 | Art-Nr. 04701
black Art-Nr. 04711 | white Art-No. 04716



UP-Touch Panel DP CAP 215
black Art-Nr. 04713 | white Art-No. 04718

Product description

Elegant and highly available

This Touch Panel PC has a capacitive touch display and features by fanless Low-Energy-technology, Hardware according to industrial standards, high performance and integrated microphone with speakers.

The Panel PC is equipped with Windows 7 embedded and a 30 GB SSD-HDD 2.5 SATA, so the device is executable and ready for use at once. As central information pool the Software Control T is preinstalled on the panel. This software combines building's visualization, Internet, E-Mail and Multimedia operation within one user interface.

Optionally an interphone can be integrated using the additional hardware module Voice Performance and the additional software HomeIntercom. Moreover it is possible to integrate a camera (with Privacy-functionality) at the Top of the chassis (accessory!). Together with the Dreambox DM600 and the additional software TV/Radio the Touchpanel even serves as TV/Radio device.

The thought out mounting system serves for a fast and simple alignment of panel and frame.

Accessory:

Wall Box DP 104 | 150 | 185 | 215

In-wall box for flush mounting in walls with 3-D-vernier adjustment

Flush mounting frame DP 104 | 150 | 185 | 215

Special mounting frame for a flush in-wall installation.



b.a.b-technologie gmbh
Inhouse Dortmund
Rosemeyerstraße 14
D-44139 Dortmund
Germany

phone: +49 231 - 476 425 - 30
fax: +49 231 - 476 425 - 59
e-mail: info@bab-tec.de
internet: www.bab-tec.de

Technical Data

UP-Touch Panel DP 104 | 150 | 185 | 215

104 = 10,4" (26,4 cm) | 150 = 15" (38,4 cm)
185 = 18,5" (47 cm) | 215 = 21,5" (54,6 cm)

- Panel-PC with capacitive touch surface
- visible image W x H (in mm):
211 x 158 | 304 x 228 | 410 x 230 | 475 x 263
- mounting frame W x H (in mm):
278 x 229 | 370 x 298 | 478 x 300 | 541 x 336
- mounting depth: 85 mm
- Stainless Steel chassis
- Weight (in kg): 2,97/4,35/6,7/8,4
- Display: TFT-Color-LED mit LED Backlight
- Resolution: 1024 x 768 / 1024 x 768 | 1366 x 786 / 1920 x 1080
- CPU Intel Atom 1,6 Ghz Dual Core;
- Cooling: fanless (convection)
- Buffer: 30 GB SSD-HDD 2.5 SATA
- Memory: 2 GB DDR2 1066
- Power consumption: max 25,5 Watt / 26,9 Watt / 32,6 Watt
- Ports:
2 x RJ-45 LAN 1 Gigabit, 1 x Serial, 1 x HDMI,
USB: Front: 1x USB 2.0 / Back: 1x USB 3.0, 2x USB 2.0
- Audio: 2 x 1 W Speakers Stereo Broadband
- 2 x 15 W Speaker Connection
- Microphone with integrated handsfree functionality
- REG Power Supply: 24 V, 2,5 A (included in delivery)

Additional hardware (optional):

- Voice Performance Module
- Camera Module
- Data backup and recovery USB-Stick

Additional software (optional):

- HomeIntercom Software for UP-Touch Panel DP
incl. Basis Module
incl. Camera Module
incl. Videophon Module
- TV/Radio Module
- Monitoring Module